



213.63336

SPINA MOBILE

63A 2P+T 7h 480-500V 50Hz 60Hz Morsetti a mantello

Certificati

TECHDATA		NORME E LEGGI	
Serie commerciale	Serie OPTIMA	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Tipologia prodotto	SPINA MOBILE	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Descrizione sintetica	SPINA MOBILE		
Tipo installazione	PORTATILE		
Corrente nominale	63A	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Poli	2P+T	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Riferimento Orario	7h		
Tensione nominale (range)	400V-up	EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Tensione nominale	480-500V		
Frequenza d'impiego	60Hz	EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Frequenza d'impiego	50Hz		
Colore	NERO	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Materiale	TERMOPLASTICO		
Grado di protezione generico	Protetto da getti d'acqua		
Grado di protezione IP	IP44/IP54		
Grado di protezione IK	IK08		
Tipo di uscite disponibili	DIRITTA		
Morsetti	Morsetti a mantello		

Materiale di contatto	CuZn (ottone)
Trattamento superficiale cont.	Nichelato
Uscita cavo	PRESSACAVO