



215.6331

SPINA MOBILE

63A 3P+T 4h 100-130V 50Hz 60Hz Morsetti a vite

Certificati

TECHDATA		NORME E LEGGI	
Tipologia prodotto	SPINA MOBILE	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Serie commerciale	Serie IEC309	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Descrizione sintetica	SPINA MOBILE		
Tipo installazione	PORTATILE		
Corrente nominale	63A	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Poli	3P+T	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Riferimento Orario	4h		
Tensione nominale (range)	50-200V	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Tensione nominale	100-130V		
Frequenza d'impiego	50Hz		
Frequenza d'impiego	60Hz		
Colore	GIALLO		
Materiale	TERMOPLASTICO		
Grado di protezione generico	Stagno all'immersione		
Grado di protezione IP	IP66/IP67		
Tipo di uscite disponibili	DIRITTA		
Morsetti	Morsetti a vite		
Materiale di contatto	CuZn (ottone)		

Trattamento superficiale cont.	Nichelato
Uscita cavo	PG36