



218.EX125365

SPINA MOBILE

125A 3P+T 11h 440-460V 60Hz II 3D Morsetti a mantello

Certificati

TECHDATA		NORME E LEGGI	
Tipologia prodotto	SPINA MOBILE	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Serie commerciale	OPTX	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Descrizione sintetica	SPINA MOBILE		
Tipo installazione	PORTATILE		
Corrente nominale	125A	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Poli	3P+T	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Riferimento Orario	11h		
Tensione nominale (range)	400V-up	EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Tensione nominale	440-460V		
Frequenza d'impiego	60Hz	EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Colore	ROSSO		
Materiale	TERMOPLASTICO	EN 60079-0 (2012)	[European Standard] Explosive atmospheres. General requirements.
Grado di protezione generico	Protetto da getti d'acqua	EN 60079-31 (2014)	[European Standard] Explosive atmospheres. Equipment dust ignition protection by enclosure "t"
Grado di protezione IP	IP66		
Tipo di uscite disponibili	DIRITTA	EN 60079-0/A11 (2013)	[European Standard] Explosive atmospheres. General requirements.
Morsetti	Morsetti a mantello	DIRECTIVE ATEX 2014/34/UE	[European Directives] Atmosphere Explosive
Materiale di contatto	CuZn (ottone)		
Trattamento superficiale cont.	Nichelato		

Uscita cavo	PRESSACAVO
Gruppo e categorie EX	II 3D