



219.63364.RU

SPINA MOBILE

63A 3P+T 3h 380V 50Hz / 440V 60Hz 50Hz
60Hz II 2GD EAC [Eurasian Conformity]

Certificati

TECHDATA		NORME E LEGGI	
Serie commerciale	Serie OPTIMA-EX[GD]	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Tipologia prodotto	SPINA MOBILE	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Descrizione sintetica	SPINA MOBILE		
Tipo installazione	PORTATILE		
Corrente nominale	63A	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Poli	3P+T	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Riferimento Orario	3h		
Tensione nominale (range)	250-400V	EN 60079-7 (2007)	[European Standard] Explosive atmospheres. Equipment protection by increased safety "e"
Tensione nominale	380V 50Hz / 440V 60Hz		
Frequenza d'impiego	60Hz	IEC 60079-7 (2006-07)	[International Standard] Explosive atmospheres - Part 7: Equipment protection by increased safety "e".
Frequenza d'impiego	50Hz	EN 60079-1 (2007)	[European Standard] Electrical apparatus for explosive gas atmospheres - Part 1: Flameproof enclosures "d"
Colore	ROSSO		
Materiale	TERMOPLASTICO	EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Grado di protezione generico	Protetto da getti d'acqua	EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Grado di protezione IP	IP66		
Tipo di uscite disponibili	DIRITTA	EN 60079-0 (2012)	[European Standard] Explosive atmospheres. General requirements.
Uscita cavo	PRESSACAVO	IEC 60079-0 (2011)	[International Standard] Electrical Apparatus for Explosive Gas Atmospheres - Part 0: General Requirements.
Gruppo e categorie EX	II 2GD	IEC 60079-1 (2007-	[International Standard] Explosive

Temperatura ambiente Ta min	-35 °C	04)	atmospheres - Part 1: Equipment protection by flameproof enclosures "d".
Temperatura ambiente Ta max	60 °C	EN 60079-31 (2014)	[European Standard] Explosive atmospheres. Equipment dust ignition protection by enclosure "t"
Opzioni	EAC [Eurasian Conformity]	IEC 60079-31 (2013)	[International Standard] Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"
		EN 60079-0/A11 (2013)	[European Standard] Explosive atmospheres. General requirements.
		DIRECTIVE ATEX 2014/34/UE	[European Directives] Atmosphere Explosive