



245.32972

SPINA DA PARETE

32A 3P+N+T 2h >50V >300-500Hz

Certificati

TECHDATA		NORME E LEGGI	
Serie commerciale	Serie OPTIMA	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Tipologia prodotto	SPINA DA PARETE	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Descrizione sintetica	SPINA DA PARETE		
Tipo installazione	PARETE		
Corrente nominale	32A	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Poli	3P+N+T	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Riferimento Orario	2h		
Tensione nominale (range)	50-200V	EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Tensione nominale	>50V		
Frequenza d'impiego	>300-500Hz	EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Colore	VERDE		
Materiale	TERMOPLASTICO	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Grado di protezione generico	Stagno all'immersione		
Grado di protezione IP	IP66/IP67/IP69		
Tipo di uscite disponibili	INCLINATA		
Uscita cavo	M32X1,5		