



423.32634

PRESA DA INCASSO

32A 2P+T 3h >50-250V Corr. continua
75X75MM Morsetti a vite

Certificati

TECHDATA		NORME E LEGGI	
Tipologia prodotto	PRESA DA INCASSO	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Serie commerciale	Serie OPTIMA	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Descrizione sintetica	PRESA DA INCASSO		
Tipo installazione	INCASSO		
Corrente nominale	32A	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Poli	2P+T	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Riferimento Orario	3h		
Tensione nominale (range)	50-200V	EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Tensione nominale	>50-250V		
Frequenza d'impiego	Corr. continua	EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Colore	GRIGIO		
Materiale	TERMOPLASTICO	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Grado di protezione generico	Protetto da getti d'acqua		
Grado di protezione IP	IP44/IP54		
Tipo di uscite disponibili	DIRITTA		
Morsetti	Morsetti a vite		
Flangia	75X75MM		