



428.16667

PRESA DA INCASSO

16A 3P+T 5h 600-690V 50Hz 60Hz 75X75MM
Morsetti a vite

Certificati

TECHDATA		NORME E LEGGI	
Serie commerciale	Serie OPTIMA	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Tipologia prodotto	PRESA DA INCASSO	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Descrizione sintetica	PRESA DA INCASSO		
Tipo installazione	INCASSO		
Corrente nominale	16A	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Poli	3P+T	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Riferimento Orario	5h		
Tensione nominale (range)	400-up	EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Tensione nominale	600-690V		
Frequenza d'impiego	60Hz	EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Frequenza d'impiego	50Hz		
Colore	NERO	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Materiale	TERMOPLASTICO		
Grado di protezione generico	Stagno all'immersione		
Grado di protezione IP	IP66/IP67/IP69		
Tipo di uscite disponibili	DIRITTA		
Morsetti	Morsetti a vite		
Flangia	75X75MM		