



428.3264

PRESA DA INCASSO

32A 3P+T 9h 200-250V 50Hz 60Hz 75X75MM
Morsetti a vite

Certificati

| TECHDATA | | NORME E LEGGI | |
|------------------------------|-----------------------|-----------------------------------|---|
| Tipologia prodotto | PRESA DA INCASSO | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Serie commerciale | Serie OPTIMA | EN 60309-2 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Descrizione sintetica | PRESA DA INCASSO | | |
| Tipo installazione | INCASSO | | |
| Corrente nominale | 32A | EN 60309-1/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Poli | 3P+T | EN 60309-2/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Riferimento Orario | 9h | | |
| Tensione nominale (range) | 200-250V | EN 60309-1/A2 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Tensione nominale | 200-250V | | |
| Frequenza d'impiego | 50Hz | EN 60309-2/A2 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Frequenza d'impiego | 60Hz | | |
| Colore | BLU | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Materiale | TERMOPLASTICO | | |
| Grado di protezione generico | Stagno all'immersione | | |
| Grado di protezione IP | IP66/IP67/IP69 | | |
| Grado di protezione IK | IK08 | | |
| Tipo di uscite disponibili | DIRITTA | | |
| Morsetti | Morsetti a vite | | |

| | |
|-----------------------|---------------|
| Materiale di contatto | CuZn (ottone) |
| Flangia | 75X75MM |