



503.AMR12587-F

PRESA INTERBLOCCATA

125A 3P+N+T 6h 346-415V Morsetti a vite Con interblocco meccanico

Certificati

TECHDATA		NORME E LEGGI	
Serie commerciale	Serie ADVANCE-GRP[AMR]	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Tipologia prodotto	PRESA INTERBLOCCATA	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Descrizione sintetica	PRESA INTERBLOCCATA		
Tipo installazione	PARETE		
Corrente nominale	125A	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Poli	3P+N+T	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Riferimento Orario	6h		
Tensione nominale (range)	250-400V	EN 60309-4 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock
Tensione nominale	346-415V		
Colore	ROSSO	EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Materiale	GRP Glass Reinforced Polyester	EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Grado di protezione generico	Protetto da getti d'acqua		
Grado di protezione IP	IP66	EN 60309-4/A1 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock
Grado di protezione IK	IK10		
Morsetti	Morsetti a vite		
Materiale di contatto	CuZn (ottone)	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Temperatura di esercizio	-40°C/+60°C	DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive
GLOW WIRE	GW 960°C		

Autoestinguenza UL94	V0
Opzioni	Con interblocco meccanico
Note	CON SEZIONATORE+FUSE
Lucchetto	ø6,3mm