



504.32876-A

PRESA INTERBLOCCATA

32A 3P+N+T 7h 480-500V 50Hz 60Hz II 2GD
 130X260MM_PAR Morsetti a vite Con
 interblocco meccanico Low temperature [-50°C]

Certificati

| TECHDATA | | NORME E LEGGI | |
|------------------------------|--------------------------------|----------------------|---|
| Serie commerciale | Serie ADVANCE-GRP[GD] | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Tipologia prodotto | PRESA INTERBLOCCATA | EN 60309-2 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Descrizione sintetica | PRESA INTERBLOCCATA | | |
| Tipo installazione | PARETE | | |
| Corrente nominale | 32A | EN 60309-1/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Poli | 3P+N+T | EN 60309-2/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Riferimento Orario | 7h | | |
| Tensione nominale (range) | 400V-up | EN 60309-4 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock |
| Tensione nominale | 480-500V | | |
| Frequenza d'impiego | 60Hz | EN 60309-1/A2 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Frequenza d'impiego | 50Hz | EN 60309-2/A2 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Colore | NERO | | |
| Materiale | GRP Glass Reinforced Polyester | EN 60309-4/A1 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock |
| Grado di protezione generico | Protetto da getti d'acqua | | |
| Grado di protezione IP | IP66 | EN 60079-31 (2014) | [European Standard] Explosive atmospheres. Equipment dust ignition protection by enclosure "t" |
| Grado di protezione IK | IK10 | | |
| Morsetti | Morsetti a vite | EN 60079-1 (2014) | [European Standard] Electrical apparatus for explosive gas atmospheres - Part 1: Flameproof enclosures 'd' |
| Materiale di contatto | CuZn (ottone) | EN 60079-7 (2015) | [European Standard] Explosive |

| | | | |
|-----------------------------|---------------------------|---------------------------|---|
| Flangia | 130X260MM_PAR | | atmospheres. Equipment protection by increased safety "e" |
| Uscita cavo | 1xM32 | EN 60079-7 (2018) | [European Standard] Explosive atmospheres. Equipment protection by increased safety "e" |
| Temperatura di esercizio | -40°C/+60°C | EN 60079-0 (2018) | [European Standard] Explosive atmospheres. General requirements. |
| GLOW WIRE | GW 960°C | DIRECTIVE ATEX 2014/34/UE | [European Directives] Atmosphere Explosive |
| Autoestinguenza UL94 | V0 | | |
| Gruppo e categorie EX | II 2GD | | |
| Temperatura ambiente Ta min | -50 °C | | |
| Temperatura ambiente Ta max | 60 °C | | |
| Opzioni | Con interblocco meccanico | | |
| Opzioni | Low temperature [-50°C] | | |
| Lucchetto | ø5mm | | |