



504.32877

PRESA INTERBLOCCATA

32A 3P+N+T 5h 600-690V 50Hz 60Hz II 2GD
130X260MM_PAR Morsetti a vite Con
interblocco meccanico

Certificati

TECHDATA		NORME E LEGGI	
Serie commerciale	Serie ADVANCE-GRP[GD]	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Tipologia prodotto	PRESA INTERBLOCCATA	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Descrizione sintetica	PRESA INTERBLOCCATA		
Tipo installazione	PARETE		
Corrente nominale	32A	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Poli	3P+N+T	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Riferimento Orario	5h		
Tensione nominale (range)	400V-up	EN 60309-4 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock
Tensione nominale	600-690V		
Frequenza d'impiego	60Hz	EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Frequenza d'impiego	50Hz	EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Colore	ROSSO		
Materiale	GRP Glass Reinforced Polyester	EN 60309-4/A1 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock
Grado di protezione generico	Protetto da getti d'acqua		
Grado di protezione IP	IP66	EN 60079-31 (2014)	[European Standard] Explosive atmospheres. Equipment dust ignition protection by enclosure "t"
Grado di protezione IK	IK10		
Morsetti	Morsetti a vite	EN 60079-1 (2014)	[European Standard] Electrical apparatus for explosive gas atmospheres - Part 1: Flameproof enclosures 'd'
Materiale di contatto	CuZn (ottone)	EN 60079-7 (2015)	[European Standard] Explosive

Flangia	130X260MM_PAR		atmospheres. Equipment protection by increased safety "e"
Uscita cavo	1xM32	EN 60079-7 (2018)	[European Standard] Explosive atmospheres. Equipment protection by increased safety "e"
Temperatura di esercizio	-40°C/+60°C	EN 60079-0 (2018)	[European Standard] Explosive atmospheres. General requirements.
GLOW WIRE	GW 960°C	DIRECTIVE ATEX 2014/34/UE	[European Directives] Atmosphere Explosive
Autoestinguenza UL94	V0		
Gruppo e categorie EX	II 2GD		
Temperatura ambiente Ta min	-35 °C		
Temperatura ambiente Ta max	60 °C		
Opzioni	Con interblocco meccanico		
Lucchetto	ø5mm		