


506.M1675

PRESA INTERBLOCCATA

16A 3P+N+T 9h 208-250V 50Hz 60Hz
136X125MM_PAR Morsetti a vite Con
interblocco meccanico



Certificati

TECHDATA		NORME E LEGGI	
Serie commerciale	Serie OMNIA	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Tipologia prodotto	PRESA INTERBLOCCATA	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Descrizione sintetica	PRESA INTERBLOCCATA		
Tipo installazione	PARETE		
Corrente nominale	16A	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Poli	3P+N+T	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Riferimento Orario	9h		
Tensione nominale (range)	200-250V	EN 60309-4 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock
Tensione nominale	208-250V		
Frequenza d'impiego	60Hz	EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Frequenza d'impiego	50Hz	EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Colore	BLU		
Materiale	TERMOPLASTICO		
Grado di protezione generico	Stagno all'immersione	EN 60309-4/A1 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock
Grado di protezione IP	IP66/IP67		
Grado di protezione IK	IK08	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Morsetti	Morsetti a vite		
Materiale di contatto	CuZn (ottone)		

Flangia	136X125MM_PAR
Opzioni	Con interblocco meccanico
Note	CON BASE PORTAFUSIBILI