

506.M3275

PRESA INTERBLOCCATA

32A 3P+N+T 9h 208-250V 50Hz 60Hz
136X125MM_PAR Morsetti a vite Con
interblocco meccanico



Certificati

| TECHDATA | | NORME E LEGGI | |
|------------------------------|-----------------------|-----------------------------------|---|
| Tipologia prodotto | PRESA INTERBLOCCATA | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Serie commerciale | Serie OMNIA | EN 60309-2 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Descrizione sintetica | PRESA INTERBLOCCATA | | |
| Tipo installazione | PARETE | | |
| Corrente nominale | 32A | EN 60309-1/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Poli | 3P+N+T | EN 60309-2/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Riferimento Orario | 9h | | |
| Tensione nominale (range) | 200-250V | EN 60309-4 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock |
| Tensione nominale | 208-250V | | |
| Frequenza d'impiego | 60Hz | EN 60309-1/A2 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Frequenza d'impiego | 50Hz | EN 60309-2/A2 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Colore | BLU | | |
| Materiale | TERMOPLASTICO | | |
| Grado di protezione generico | Stagno all'immersione | EN 60309-4/A1 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock |
| Grado di protezione IP | IP66/IP67 | | |
| Grado di protezione IK | IK08 | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Morsetti | Morsetti a vite | | |
| Materiale di contatto | CuZn (ottone) | | |

| | |
|---------|---------------------------|
| Flangia | 136X125MM_PAR |
| Opzioni | Con interblocco meccanico |
| Note | CON BASE PORTAFUSIBILI |