



513.1653-2AFS

PRESA DA PARETE

16A 6h 2P+T 200-250V 2 NR ARGENTINA IP44 /IP54

Certificati

TECHDATA		NORME E LEGGI	
Serie commerciale	Serie OPTIMA-COMBI	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Tipologia prodotto	PRESA DA PARETE	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Descrizione sintetica	PRESA DA PARETE		
Corrente nominale	16A		
Poli	2P+T	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Riferimento Orario	6h	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Tensione nominale (range)	200-250V		
Tensione nominale	200-250V	EN 60309-4 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock
Frequenza d'impiego	60Hz		
Frequenza d'impiego	50Hz	EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Colore	BLU	EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Materiale	TERMOPLASTICO		
Materiale di contatto	CuZn (ottone)		
Grado di protezione generico	Protetto da getti d'acqua	EN 60309-4/A1 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock
Grado di protezione IP	IP44/IP54		
Grado di protezione IK	IK08	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Tipo di uscite disponibili	INCLINATA		
Morsetti	Morsetti a vite		

Uscita cavo	M32X1,5
Tipo	ARGENTINA
N° uscite disponibili	2 NR
Opzioni	Presca combinata