Scheda tecnica prodotto

21 feb 2022 17:42



546.1687

PRESA INTERBLOCCATA

16A 3P+N+T 6h 346-415V 50Hz 60Hz Morsetti a vite Con interblocco meccanico

Certificati

TECHDATA	
Serie commerciale	Serie QUADRA
Tipologia prodotto	PRESA INTERBLOCCATA
Descrizione sintetica	PRESA INTERBLOCCATA
Tipo installazione	PARETE
Corrente nominale	16A
Poli	3P+N+T
Riferimento Orario	6h
Tensione nominale (range)	250-400V
Tensione nominale	346-415V
Frequenza d'impiego	60Hz
Frequenza d'impiego	50Hz
Colore	ROSSO
Materiale	TERMOPLASTICO
Grado di protezione generico	Stagno all'immersione
Grado di protezione IP	IP67
Grado di protezione IK	IK07
Morsetti	Morsetti a vite
Materiale di contatto	CuZn (ottone)

NORME E LEGGI	
EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive

Uscita cavo	PG21
Opzioni	Con interblocco meccanico
Note	SENZA BASE PORTAFUSIBILI