



# 590.SGE16005-C

## COMMUTATORE IN CASSETTA

160A 3P+N IP65 300x400x150mm C3 IK10  
GENERALE GRIGIO/NERO

Certificati

TECHDATA		NORME E LEGGI	
Serie commerciale	Serie ISOLATORS-INOX	EN 60947-3 (2009)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Tipologia prodotto	COMMUTATORE IN CASSETTA	EN 60947-1 (2007)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Descrizione sintetica	COMMUTATORE IN CASSETTA	EN 60947-1/A1 (2011)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Materiale	ACCIAIO INOX [AISI304L]	EN 60947-3/A1 (2012)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Grado di protezione IP	IP65	EN 60947-1/A2 (2014)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Tipo	GENERALE	EN 60947-3/A2 (2015)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Colore	GRIGIO/NERO	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Corrente nominale	160A		
Poli	3P+N		
Taglia interruttore	C3		
Tensione nominale	690V		
Dimensioni	300x400x150mm		
Grado di protezione IK	IK10		