



592.R001-03-P

INTERRUTTORE BIPOLARE

INTERRUTTORE BIPOLARE 16AX

1xM20+2xM20 II 2GD -35 °C 60 °C

Certificati

TECHDATA		NORME E LEGGI	
Serie commerciale	Serie ROCKER-EX[GD]	EN 60079-0 (2012)	[European Standard] Explosive atmospheres. General requirements.
Tipologia prodotto	INTERRUTTORE BIPOLARE	EN 60079-31 (2014)	[European Standard] Explosive atmospheres. Equipment dust ignition protection by enclosure "t"
Descrizione sintetica	INTERRUTTORE BIPOLARE	IEC 60079-31 (2013)	[International Standard] Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"
Tipo installazione	PARETE	EN 60079-0/A11 (2013)	[European Standard] Explosive atmospheres. General requirements.
Grado di protezione generico	Protetto da getti d'acqua	EN 60079-1 (2014)	[European Standard] Electrical apparatus for explosive gas atmospheres - Part 1: Flameproof enclosures 'd'
Grado di protezione IP	IP66	EN 60079-7 (2015)	[European Standard] Explosive atmospheres. Equipment protection by increased safety "e"
Materiale	TERMOPLASTICO	IEC 60079-1 (2014)	[International Standard] Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d".
Corrente nominale	16AX	EN 60669-1 (2018)	[European Standard] Switches for household and similar fixed-electrical installations. Part 1: General requirements
Tensione nominale	250V	IEC 60669-1 (2017)	[International Standard] Switches for household and similar fixed-electrical installations. - Part 1: General requirements.
Note	1xM20+2xM20	IEC 60079-0 (2017)	[International Standard] Explosive atmospheres - Part 0: Equipment - General requirements
Gruppo e categorie EX	II 2GD	IEC 60079-7 (2017)	[International Standard] Explosive atmospheres - Part 7: Equipment protection by increased safety "e".
Temperatura ambiente Ta min	-35 °C	EN 60079-7 (2018)	[European Standard] Explosive atmospheres. Equipment protection by increased safety "e"
Temperatura ambiente Ta max	60 °C	DIRECTIVE ATEX 2014/34/UE	[European Directives] Atmosphere Explosive