



899.AS2PR450V

SPINA MOBILE

250A 3P+N+T 1000V Morsetti a vite

Certificati

| TECHDATA | | NORME E LEGGI | |
|--------------------------------|---------------------------|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Tipologia prodotto | SPINA MOBILE | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Serie commerciale | Serie OPTIMA-METAL | EN 60309-2 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Descrizione sintetica | SPINA MOBILE | | |
| Tipo installazione | PORTATILE | | |
| Corrente nominale | 250A | EN 60309-1/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Poli | 3P+N+T | EN 60309-2/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Tensione nominale (range) | 400V-up | | |
| Tensione nominale | 1000V | EN 60309-1/A2 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Materiale | LEGA ALLUMINIO PRESSOFUSO | EN 60309-2/A2 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Grado di protezione generico | Stagno all'immersione | | |
| Grado di protezione IP | IP67 | | |
| Grado di protezione IK | IK10 | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Morsetti | Morsetti a vite | | |
| Materiale di contatto | CuZn (ottone) | | |
| Trattamento superficiale cont. | Argentato | | |
| Sezione cavo | 50-70 mm ² | | |