

Article

213.3236F.K
 PLUG 3P+E IP44 32A 6h 380-415V AC

Picture**Master data**

Minimum order	10 NR
Net Weight	0.248 KG
EAN code	8001636242705
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	OPTIMA Series
Synthetical description	PLUG
Rated current	32A
Poles	3P+E
Hour position	6h
Rated voltage	380-415V
Working frequency	50Hz
Working frequency	60Hz
Colour	RED
Protection degree IP	IP44/IP54
Types of available outlets	STRAIGHT
Terminals	Spring terminals
Cable outlet	CABLE GLAND

Approvals and Certifications

EAC
 Eurasian Conformity



UE
 Declaration of conformity

Standards and Laws

EN 60309-2/A1 (2007)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2 (1999)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 2:
 Dimensional interchangeability requirements
 for pin and contact-tube accessories of
 harmonized configurations



EN 60309-1/A1 (2007)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 1:
 General requirements



EN 60309-2/A2 (2012)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 2:
 Dimensional interchangeability requirements
 for pin and contact-tube accessories of
 harmonized configurations



EN 60309-1/A2 (2012)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 1:
 General requirements

Packaging

Description	Carton
Quantity	40
EAN code	8001636690322
Gross weight	11 KG
Volume	50119.662 CCM
Dimensions	397x397x318 (MM)
Description	Box
Quantity	10
EAN code	8001636690315
Gross weight	2.75 KG
Volume	9680 CCM
Dimensions	220x275x160 (MM)

Annexed



Instruction manual



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

Note:

Black-coloured

