

Article**218.125361**

PLUG 3P+E IP66/IP67 125A 10h >50V AC

Picture**Master data**

Minimum order	1 NR
Net Weight	1.131 KG
EAN code	8001636273426
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	OPTIMA Series
Synthetical description	PLUG
Rated current	125A
Poles	3P+E
Hour position	10h
Rated voltage	>50V
Working frequency	100-300Hz
Colour	GREEN
Protection degree IP	IP66/IP67/IP69
Types of available outlets	STRAIGHT
Terminals	Mantle terminals
Cable outlet	CABLE GLAND

Approvals and Certifications

UE
Declaration of conformity



I.M.Q. - ENEC 03
European Norms Electrical Certification



EAC
Eurasian Conformity

Standards and Laws

EN 60309-1 (1999)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2 (1999)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A1 (2007)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 1:
 General requirements



EN 60309-2/A1 (2007)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 2:
 Dimensional interchangeability requirements
 for pin and contact-tube accessories of
 harmonized configurations



EN 60309-1/A2 (2012)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 1:
 General requirements



EN 60309-2/A2 (2012)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 2:
 Dimensional interchangeability requirements
 for pin and contact-tube accessories of
 harmonized configurations

Packaging

Description	Carton
Quantity	8
EAN code	8001636723266
Gross weight	10.896 KG
Volume	87100 CCM
Dimensions	400x650x335 (MM)
Description	Box
Quantity	1
EAN code	
Gross weight	1.362 KG
Volume	7497 CCM
Dimensions	140x315x170 (MM)

Annexed



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]