

Article

248.1696.K
 APPLIANCE INLET 3P+E IP66/IP67 16A 6h

Picture**Master data**

Minimum order	10 NR
Net Weight	0.149 KG
EAN code	8001636223759
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	OPTIMA Series
Synthetical description	FLUSH MOUNTING APPLIANCE INLET
Rated current	16A
Poles	3P+E
Hour position	6h
Rated voltage	380-415V
Working frequency	50Hz
Working frequency	60Hz
Colour	RED
Protection degree IP	IP66/IP67/IP69
Types of available outlets	STRAIGHT
Terminals	Screw terminals
Flange	75X75MM

Approvals and Certifications

UE
 Declaration of conformity



EAC
 Eurasian Conformity

Standards and Laws

EN 60309-1 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations

Packaging**Annexed**

Description	Carton
Quantity	50
EAN code	8001636674223
Gross weight	8.85 KG
Volume	46878.5 CCM
Dimensions	305x580x265 (MM)
Description	Box
Quantity	10
EAN code	8001636674216
Gross weight	1.77 KG
Volume	7128 CCM
Dimensions	220x270x120 (MM)



Technical drawing [DWG]

.dwg



Technical drawing [PDF]

.pdf



Technical drawing [STP]

.stp

Note:

Black-coloured

