

Article**248.3296RV**

OPTIMA REVERSE 3P+E 32A IP66/67 PLUG

Picture**Master data**

Minimum order	10 NR
Net Weight	0.222 KG
EAN code	8001636234656
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	OPTIMA-REVERSE Series
Synthetical description	FLUSH MOUNTING APPLIANCE INLET
Rated current	32A
Poles	3P+E
Hour position	6h
Rated voltage	380-415V
Working frequency	50Hz
Working frequency	60Hz
Colour	RED
Protection degree IP	IP66/IP67/IP69
Types of available outlets	STRAIGHT
Terminals	Screw terminals
Flange	75X75MM

Approvals and Certifications

UE
Declaration of conformity



EAC
Eurasian Conformity

Standards and Laws

EN 60309-1 (1999)
[European Standard] Plugs, socket-outlets
and couplers for industrial purposes. Part 1:
General requirements



EN 60309-2 (1999)
[European Standard] Plugs, socket-outlets
and couplers for industrial purposes. Part 2:
Dimensional interchangeability requirements
for pin and contact-tube accessories of
harmonized configurations



EN 60309-1/A1 (2007)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 1:
 General requirements



EN 60309-2/A1 (2007)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 2:
 Dimensional interchangeability requirements
 for pin and contact-tube accessories of
 harmonized configurations

Packaging

Description	Carton
Quantity	50
EAN code	8001636686400
Gross weight	12.85 KG
Volume	66990 CCM
Dimensions	385x580x300 (MM)
Description	Box
Quantity	10
EAN code	8001636686394
Gross weight	2.57 KG
Volume	9450.54 CCM
Dimensions	258x333x110 (MM)

Annexed



Instruction manual



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

Note:

> Phase inverter



> Operating principle of the phase inverter



Articoli Collegati:

	570.90324	PLUG CAP 2/3P+E 30A 32A GREY
--	-----------	------------------------------