

Article**504.1687**

INTERLOCKED SOCKET 3P+N+E IP66 16A 6h

Picture**Master data**

Minimum order	1 NR
Net Weight	2.738 KG
EAN code	8001636294193
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	ADVANCE-GRP[GD] Series
Synthetical description	INTERLOCKED SOCKET
Rated current	16A
Poles	3P+N+E
Hour position	6h
Rated voltage	346-415V
Working frequency	50Hz
Working frequency	60Hz
Colour	RED
Protection degree IP	IP66
Flange	130X260MM_PAR
Cable outlet	1xM25
Group and categories EX	II 2 GD
Ambient temperature Ta min	-35 °C
Ambient temperature Ta max	60 °C

Approvals and Certifications
 UE
 Declaration of conformity

 Notifica ATEX e IECEX
 Notifica ATEX e IECEX
Standards and Laws
 EN 60309-1 (1999)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 1:
 General requirements



Notifica ATEX e IECEx
Notifica ATEX e IECEx



INERIS ATEX
Institut National de l'Environnement
Industriel et des Risques



INERIS IECEx
Institut National de l'Environnement
Industriel et des Risques



EN 60309-2 (1999)
[European Standard] Plugs, socket-outlets
and couplers for industrial purposes. Part 2:
Dimensional interchangeability requirements
for pin and contact-tube accessories of
harmonized configurations



EN 60309-1/A1 (2007)
[European Standard] Plugs, socket-outlets
and couplers for industrial purposes. Part 1:
General requirements



EN 60309-2/A1 (2007)
[European Standard] Plugs, socket-outlets
and couplers for industrial purposes. Part 2:
Dimensional interchangeability requirements
for pin and contact-tube accessories of
harmonized configurations



EN 60309-4 (2007)
[European Standard] Plugs, socket-outlets
and couplers for industrial purposes.
Switched socket-outlets and connectors,
with or without interlock



EN 60309-1/A2 (2012)
[European Standard] Plugs, socket-outlets
and couplers for industrial purposes. Part 1:
General requirements



EN 60309-2/A2 (2012)
[European Standard] Plugs, socket-outlets
and couplers for industrial purposes. Part 2:
Dimensional interchangeability requirements
for pin and contact-tube accessories of
harmonized configurations



EN 60309-4/A1 (2012)
[European Standard] Plugs, socket-outlets
and couplers for industrial purposes. -
Switched socket-outlets and connectors,
with or without interlock



EN 60079-0 (2012)
[European Standard] Explosive
atmospheres. General requirements.



IEC 60079-0:2011
[International Standard] Electrical Apparatus
for Explosive Gas Atmospheres - Part 0:
General Requirements.



EN 60079-31 (2014)
[European Standard] Explosive
atmospheres. Equipment dust ignition
protection by enclosure "t"



IEC 60079-31 (2013)
[International Standard] Explosive
atmospheres - Part 31: Equipment dust
ignition protection by enclosure "t"



EN 60079-0/A11 (2013)
[European Standard] Explosive
atmospheres. General requirements.



EN 60079-1 (2014)
[European Standard] Electrical apparatus
for explosive gas atmospheres - Part 1:
Flameproof enclosures 'd'



EN 60079-7 (2015)
[European Standard] Explosive
atmospheres. Equipment protection by
increased safety "e"



IEC 60079-1(2014)
[International Standard] Explosive
atmospheres - Part 1: Equipment protection
by flameproof enclosures "d".



IEC 60079-7(2015)
[International Standard] Explosive
atmospheres - Part 7: Equipment protection
by increased safety "e".

Packaging

Description	Box
Quantity	1
EAN code	
Gross weight	2.867 KG
Volume	7227.5 CCM
Dimensions	140x295x175 (MM)

Annexed



Instruction manual



Instruction manual



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

Note:



ATEX [ATmosphères EXplosibles]:
por applications in potentially
explosive atmospheres.

