

Article**513.1656-2FNR**

OPTIMA-COMBI C/INT. I/0/II REV. 16A 3P+E

Picture**Master data**

Minimum order	1 NR
Net Weight	0.956 KG
EAN code	8001636307961
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	OPTIMA-COMBI Series
Synthetical description	SURFACE MOUNTING SOCKET
Rated current	16A
Poles	3P+E
Hour position	6h
Rated voltage	380-415V
Working frequency	50Hz
Working frequency	60Hz
Colour	RED
Protection degree IP	IP54
Types of available outlets	ANGLED
Terminals	Screw terminals
Cable outlet	M32X1,5
Type	FRENCH
No. of available outlets	2

Approvals and Certifications
 UE
 Declaration of conformity

 EAC
 Eurasian Conformity
Standards and Laws
 EN 60309-1 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A1 (2007)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A1 (2007)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-4 (2007)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock



EN 60309-1/A2 (2012)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A2 (2012)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-4/A1 (2012)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock

Packaging

Description	Carton
Quantity	6
EAN code	8001636765662
Gross weight	6.3 KG
Volume	41571.5 CCM
Dimensions	305x580x235 (MM)
Description	Box
Quantity	1
EAN code	
Gross weight	1.05 KG
Volume	0
Dimensions	0x0x0 ()

Annexed



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

Note:

- > Open threaded cable entry 
- > COMBI version: combining industrial and household sockets 
- > Rubber threaded cable sleeve included 
- > REVERSE L-0-R: With phase reversing switch 