

Article**513.3253TS.A**

SURF.MNT.SOCKET 2P+E IP44 32A 6h

Picture**Master data**

Minimum order	1 NR
Net Weight	0.591 KG
EAN code	8001636309644
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	OPTIMA-TOP Series
Synthetical description	SURFACE MOUNTING SOCKET
Rated current	32A
Poles	2P+E
Hour position	6h
Rated voltage	200-250V
Working frequency	50Hz
Working frequency	60Hz
Colour	BLUE
Protection degree IP	IP44/IP54
Types of available outlets	ANGLED
Terminals	Screw terminals
Cable outlet	M25X1,5

Approvals and Certifications
 UE
 Declaration of conformity

 EAC
 Eurasian Conformity
Standards and Laws
 EN 60309-1 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements

 EN 60309-2 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A1 (2007)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 1:
 General requirements



EN 60309-2/A1 (2007)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 2:
 Dimensional interchangeability requirements
 for pin and contact-tube accessories of
 harmonized configurations



EN 60309-4 (2007)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes.
 Switched socket-outlets and connectors,
 with or without interlock



EN 60309-1/A2 (2012)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 1:
 General requirements



EN 60309-2/A2 (2012)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 2:
 Dimensional interchangeability requirements
 for pin and contact-tube accessories of
 harmonized configurations



EN 60309-4/A1 (2012)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. -
 Switched socket-outlets and connectors,
 with or without interlock

Packaging

Description	Carton
Quantity	6
EAN code	8001636764962
Gross weight	4.686 KG
Volume	36012.5 CCM
Dimensions	250x335x430 (MM)
Description	Box
Quantity	1
EAN code	
Gross weight	0.781 KG
Volume	3833.027 CCM
Dimensions	163x183x128.5 (MM)

Annexed



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

Note:

- > Open threaded cable entry 
- > Rubber threaded cable sleeve included 
- > Threaded cap/cable sleeve included 