

Article

513.63574T
 SOCKET IP44

Picture**Master data**

Minimum order	4 NR
Net Weight	0 KG
EAN code	8001636337333
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	OPTIMA-TOP Series
Synthetical description	SURFACE MOUNTING SOCKET
Rated current	63A
Poles	3P+N+E
Hour position	3h
Rated voltage	380V 50Hz / 440V 60Hz
Working frequency	50Hz
Working frequency	60Hz
Colour	RED
Protection degree IP	IP44
Types of available outlets	ANGLED
Terminals	Mantle terminals
Cable outlet	M40X1,5

Approvals and Certifications

UE
 Declaration of conformity



EAC
 Eurasian Conformity

Standards and Laws

EN 60309-1 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A1 (2007)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 1:
 General requirements



EN 60309-2/A1 (2007)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 2:
 Dimensional interchangeability requirements
 for pin and contact-tube accessories of
 harmonized configurations



EN 60309-1/A2 (2012)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 1:
 General requirements



EN 60309-2/A2 (2012)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 2:
 Dimensional interchangeability requirements
 for pin and contact-tube accessories of
 harmonized configurations

Packaging

Description	Carton
Quantity	4
EAN code	8001636765587
Gross weight	0 KG
Volume	28800 CCM
Dimensions	300x400x240 (MM)

Annexed



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

Note:

- > Open threaded cable entry 
- > Cable gland included 
- > Threaded cap/cable sleeve included 