

Article**515.12556**

SOCKET OUTLET 3P+E IP67 125A 6h 380-415V

Picture**Master data**

Minimum order	1 NR
Net Weight	1.865 KG
EAN code	8001636007649
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	OPTIMA Series
Synthetical description	SURFACE MOUNTING SOCKET
Rated current	125A
Poles	3P+E
Hour position	6h
Rated voltage	380-415V
Working frequency	50Hz
Working frequency	60Hz
Colour	RED
Protection degree IP	IP66/IP67
Types of available outlets	ANGLED
Cable outlet	PG 48

Approvals and Certifications**Standards and Laws**

EN 60309-1 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A1 (2007)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 1:
 General requirements



EN 60309-2/A1 (2007)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 2:
 Dimensional interchangeability requirements
 for pin and contact-tube accessories of
 harmonized configurations

Packaging

Description	Carton
Quantity	8
EAN code	8001636951683
Gross weight	17.176 KG
Volume	100188 CCM
Dimensions	360x460x605 (MM)
Description	Box
Quantity	1
EAN code	8001636939742
Gross weight	2.147 KG
Volume	9652.5 CCM
Dimensions	150x390x165 (MM)

Annexed



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

Note:



Versions also available in a metric
 cable inlet.

