

Article**515.6358**

SOCKET OUTLET 2P+E IP67 63A 9h 380-415V

Picture**Master data**

Minimum order	6 NR
Net Weight	0.956 KG
EAN code	8001636007748
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	OPTIMA Series
Synthetical description	SURFACE MOUNTING SOCKET
Rated current	63A
Poles	2P+E
Hour position	9h
Rated voltage	380-415V
Working frequency	50Hz
Working frequency	60Hz
Colour	RED
Protection degree IP	IP66/IP67
Types of available outlets	ANGLED
Cable outlet	PG 29

Approvals and Certifications**Standards and Laws**

EN 60309-1 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A1 (2007)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 1:
 General requirements



EN 60309-2/A1 (2007)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 2:
 Dimensional interchangeability requirements
 for pin and contact-tube accessories of
 harmonized configurations

Packaging

Description	Carton
Quantity	12
EAN code	8001636585307
Gross weight	12.996 KG
Volume	61600.5 CCM
Dimensions	405x585x260 (MM)
Description	Box
Quantity	6
EAN code	8001636992266
Gross weight	6.498 KG
Volume	22015.798 CCM
Dimensions	268x343x239.5 (MM)

Annexed



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

Note:



Versions also available in a metric
 cable inlet.

