

Article**518.12550T**

SURF.MNT.SOCKET 2P+E IP66/IP67 125A 4h

Picture**Master data**

Minimum order	1 NR
Net Weight	1.616 KG
EAN code	8001636319117
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	OPTIMA-TOP Series
Synthetical description	SURFACE MOUNTING SOCKET
Rated current	125A
Poles	2P+E
Hour position	4h
Rated voltage	100-130V
Working frequency	50Hz
Working frequency	60Hz
Colour	YELLOW
Protection degree IP	IP66/IP67/IP69
Types of available outlets	ANGLED
Terminals	Mantle terminals
Cable outlet	M63X1,5

Approvals and Certifications

UE
Declaration of conformity



I.M.Q. - ENEC 03
European Norms Electrical Certification



EAC
Eurasian Conformity

Standards and Laws

EN 60309-1 (1999)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2 (1999)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A1 (2007)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 1:
 General requirements



EN 60309-2/A1 (2007)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 2:
 Dimensional interchangeability requirements
 for pin and contact-tube accessories of
 harmonized configurations



EN 60309-1/A2 (2012)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 1:
 General requirements



EN 60309-2/A2 (2012)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 2:
 Dimensional interchangeability requirements
 for pin and contact-tube accessories of
 harmonized configurations

Packaging

Description	Carton
Quantity	4
EAN code	8001636756189
Gross weight	8.16 KG
Volume	72450 CCM
Dimensions	375x560x345 (MM)
Description	Box
Quantity	1
EAN code	
Gross weight	2.04 KG
Volume	14857.92 CCM
Dimensions	268x308x180 (MM)

Annexed



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

Note:



Open threaded cable entry



Cable gland included



Threaded cap/cable sleeve included

