

Article**518.1658TF**

SURF.MNT.SOCKET 2P+E IP66/IP67 16A 9h

Picture**Master data**

Minimum order	10 NR
Net Weight	0.236 KG
EAN code	8001636245461
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	OPTIMA-TOP Series
Synthetical description	SURFACE MOUNTING SOCKET
Rated current	16A
Poles	2P+E
Hour position	9h
Rated voltage	380-415V
Working frequency	50Hz
Working frequency	60Hz
Colour	RED
Protection degree IP	IP66/IP67/IP69
Types of available outlets	ANGLED
Terminals	Spring terminals
Cable outlet	M20X1,5

Approvals and Certifications
 UE
 Declaration of conformity

 EAC
 Eurasian Conformity
Standards and Laws
 EN 60309-1 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements

 EN 60309-2 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A1 (2007)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 1:
 General requirements



EN 60309-2/A1 (2007)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 2:
 Dimensional interchangeability requirements
 for pin and contact-tube accessories of
 harmonized configurations

Packaging

Description	Carton
Quantity	40
EAN code	8001636693781
Gross weight	11.28 KG
Volume	72450 CCM
Dimensions	375x560x345 (MM)
Description	Box
Quantity	10
EAN code	8001636693774
Gross weight	2.82 KG
Volume	14857.92 CCM
Dimensions	268x308x180 (MM)

Annexed



Instruction manual



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

Note:

Threaded break-through knock out

