

Article**518.63536T**

SURF.MNT.SOCKET 2P+E IP66/IP67 63A 7h

Picture**Master data**

Minimum order	4 NR
Net Weight	0 KG
EAN code	8001636024141
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	OPTIMA-TOP Series
Synthetical description	SURFACE MOUNTING SOCKET
Rated current	63A
Poles	2P+E
Hour position	7h
Rated voltage	480-500V
Working frequency	50Hz
Working frequency	60Hz
Colour	BLACK
Protection degree IP	IP66/IP67/IP69
Types of available outlets	ANGLED
Terminals	Mantle terminals
Cable outlet	M40X1,5

Approvals and Certifications

UE
Declaration of conformity



I.M.Q. - ENEC 03
European Norms Electrical Certification



EAC
Eurasian Conformity

Standards and Laws

EN 60309-1 (1999)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2 (1999)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A1 (2007)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 1:
 General requirements



EN 60309-2/A1 (2007)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 2:
 Dimensional interchangeability requirements
 for pin and contact-tube accessories of
 harmonized configurations



EN 60309-1/A2 (2012)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 1:
 General requirements



EN 60309-2/A2 (2012)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 2:
 Dimensional interchangeability requirements
 for pin and contact-tube accessories of
 harmonized configurations

Packaging

Description	Carton
Quantity	4
EAN code	8001636945477
Gross weight	0 KG
Volume	28800 CCM
Dimensions	300x400x240 (MM)

Annexed



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

Note:

- > Open threaded cable entry 
- > Cable gland included 
- > Threaded cap/cable sleeve included 