

Article**522.3254**

SOCKET OUTLET 3P+E IP44 32A 9h 200-250V

Picture**Master data**

Minimum order	10 NR
Net Weight	0.308 KG
EAN code	8001636073002
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	OPTIMA Series
Synthetical description	SURFACE MOUNTING SOCKET
Rated current	32A
Poles	3P+E
Hour position	9h
Rated voltage	200-250V
Working frequency	50Hz
Working frequency	60Hz
Colour	BLUE
Protection degree IP	IP44/IP54
Types of available outlets	STRAIGHT
Terminals	Screw terminals
Cable outlet	DRILLING POINT MARK

Approvals and Certifications
 UE
 Declaration of conformity

 I.M.Q. - ENEC 03
 European Norms Electrical Certification

 EAC
 Eurasian Conformity
Standards and Laws
 EN 60309-1 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements

 EN 60309-2 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A1 (2007)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 1:
 General requirements



EN 60309-2/A1 (2007)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 2:
 Dimensional interchangeability requirements
 for pin and contact-tube accessories of
 harmonized configurations



EN 60309-1/A2 (2012)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 1:
 General requirements



EN 60309-2/A2 (2012)
 [European Standard] Plugs, socket-outlets
 and couplers for industrial purposes. Part 2:
 Dimensional interchangeability requirements
 for pin and contact-tube accessories of
 harmonized configurations

Packaging

Description	Carton
Quantity	40
EAN code	8001636886794
Gross weight	14 KG
Volume	77123.75 CCM
Dimensions	355x550x395 (MM)
Description	Box
Quantity	10
EAN code	8001636886800
Gross weight	3.5 KG
Volume	14857.92 CCM
Dimensions	268x308x180 (MM)

Annexed



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

Note:



Blank side with drilling point mark



Rubber cable sleeve included

