

Article**560.16834**

INTERLOCKED SOCKET 2P+E IP44 16A 3h

Picture**Master data**

Minimum order	1 NR
Net Weight	0.802 KG
EAN code	8001636155661
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	ADVANCE 2 Series
Synthetical description	INTERLOCKED SOCKET
Rated current	16A
Poles	2P+E
Hour position	3h
Rated voltage	>50-250V
Working frequency	DC
Colour	GREY
Protection degree IP	IP44
Flange	106X240MM
Cable outlet	M25X1,5

Approvals and Certifications

UE
Declaration of conformity



EAC
Eurasian Conformity

Standards and Laws

EN 60309-1 (1999)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2 (1999)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations

Packaging

Description	Carton
Quantity	12

Annexed

Instruction manual

EAN code	8001636588452
Gross weight	11.436 KG
Volume	70840 CCM
Dimensions	280x440x575 (MM)
Description	Box
Quantity	1
EAN code	
Gross weight	0.953 KG
Volume	4743.75 CCM
Dimensions	115x275x150 (MM)



Technical drawing [DWG]








Technical drawing [PDF]




Technical drawing [STP]

Note:

- > Open threaded cable entry 
- > When using DC we recommend that you make sure of implementing the protection scheme that is most suitable for the system involved; contact Scame Technical Service for further information. 
- > Supplied with stainless steel fixing screws. 
- > Cable gland included 
- > Threaded cap/cable sleeve included 

Articoli Collegati:

	576.4300	MODULAR BASE ADVANCE 2
--	----------	------------------------