

Article**562.3283**

INTERLOCKED SOCKET 2P+E IP44 32A 6h

Picture**Master data**

Minimum order	1 NR
Net Weight	1.039 KG
EAN code	8001636154190
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	ADVANCE 2 Series
Synthetical description	INTERLOCKED SOCKET
Rated current	32A
Poles	2P+E
Hour position	6h
Rated voltage	200-250V
Working frequency	50Hz
Working frequency	60Hz
Colour	BLUE
Protection degree IP	IP44
Flange	106X240MM
Cable outlet	M25X1,5

Approvals and Certifications

UE
Declaration of conformity



I.M.Q. - ENEC 03
European Norms Electrical Certification



EAC
Eurasian Conformity



CQC (China)
China Quality Certification mark

Standards and Laws

EN 60309-1 (1999)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2 (1999)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A1 (2007)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A1 (2007)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-4 (2007)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock



EN 60309-1/A2 (2012)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A2 (2012)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations

Packaging

Description	Carton
Quantity	12
EAN code	8001636586021
Gross weight	14.496 KG
Volume	70840 CCM
Dimensions	280x440x575 (MM)

Description	Box
Quantity	1
EAN code	8001636586014
Gross weight	1.208 KG
Volume	4743.75 CCM
Dimensions	115x275x150 (MM)

Annexed



Instruction manual



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]



Note:

- > Open threaded cable entry 
- > Cable gland included 
- > Threaded cap/cable sleeve included 
- > Fuses not supplied 
- > Supplied with stainless steel fixing screws. 

Articoli Collegati:

	576.4300	MODULAR BASE ADVANCE 2
--	----------	------------------------