

Article**562.32833**

INTERLOCKED SOCKET 2P+E IP44 32A 12h

Picture**Master data**

Minimum order	1 NR
Net Weight	0 KG
EAN code	8001636156552
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	ADVANCE 2 Series
Synthetical description	INTERLOCKED SOCKET
Rated current	32A
Poles	2P+E
Hour position	12h
Rated voltage	TST>50V
Working frequency	50Hz
Working frequency	60Hz
Colour	GREY
Protection degree IP	IP44
Flange	106X240MM
Cable outlet	M25X1,5

Approvals and Certifications
 UE
 Declaration of conformity

 I.M.Q. - ENEC 03
 European Norms Electrical Certification

 EAC
 Eurasian Conformity
Standards and Laws
 EN 60309-1 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements

 EN 60309-2 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations

 EN 60309-1/A1 (2007)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A1 (2007)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-4 (2007)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock



EN 60309-1/A2 (2012)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A2 (2012)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations

Packaging

Description	Carton
Quantity	12
EAN code	8001636590233
Gross weight	0 KG
Volume	0
Dimensions	0x0x0 ()
Description	Box
Quantity	1
EAN code	8001636590226
Gross weight	0 KG
Volume	0
Dimensions	0x0x0 ()

Annexed



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

Note:

- > Open threaded cable entry ☒
- > Cable gland included ☒
- > Threaded cap/cable sleeve included ☒
- > Fuses not supplied ☒
- > Supplied with stainless steel fixing screws. ☒

Articoli Collegati:

	576.4300	MODULAR BASE ADVANCE 2
--	----------	------------------------