

Article**590.KEM63003**

SWITCH DISCONNECTOR 630A 3P IP65

Picture**Master data**

Minimum order	1 NR
Net Weight	18.3 KG
EAN code	8001636304991
Harmonized System Code (HSCode)	85365080

TechData

Commercial series	ISOLATORS Series
Synthetical description	SWITCH DISCONNECTOR
Protection degree IP	IP65
Type	EMERGENCY
Colour	YELLOW/RED
Rated current	630A
Poles	3P
Switch size	K4
Dimensions	400x600x200mm

Approvals and Certifications

UE
Declaration of conformity



EAC
Eurasian Conformity



TÜV NORD
Technischer Überwachungsverein

Standards and Laws

EN 60947-3 (2006)
[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units



EN 60947-1 (2007)
[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules



EN 60947-1/A1 (2011)
[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules



EN 60947-3/A1 (2011)
[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units



EN 60947-1/A2 (2014)
 [European Standard] Low-voltage
 switchgear and controlgear - Part 1: General
 rules



EN 60947-3/A2 (2015)
 [European Standard] Low-voltage
 switchgear and controlgear Part 3:
 Switches, disconnectors, switch-
 disconnectors and fuse-combination units

Packaging

Description	Carton
Quantity	1
EAN code	
Gross weight	19.45 KG
Volume	87100 CCM
Dimensions	400x650x335 (MM)

Annexed



Instruction manual



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]



Note:

> Handle padlockable in OFF only (3
 padlocks)



> TOP/BOTTOM = Top/Bottom
 connection



> Equipped with door interlock



> Gland plate cable entry

