

Article**590.KEMD20005**

SWITCH DISCONNECTOR IP65 200A 3P+N

Picture**Master data**

Minimum order	1 NR
Net Weight	0 KG
EAN code	8001636026695
Harmonized System Code (HSCode)	85365080

TechData

Commercial series	ISOLATORS Series
Synthetical description	SWITCH DISCONNECTOR
Protection degree IP	IP65
Type	EMERGENCY
Colour	YELLOW/RED
Rated current	200A
Poles	3P+N
Switch size	KF3
Fuse type	DIN-NH
Dimensions	400x600x200mm
Notes	FUSE: DIN-NH

Approvals and Certifications

UE
Declaration of conformity



EAC
Eurasian Conformity

Standards and Laws

EN 60947-3 (2006)
[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units



EN 60947-1 (2007)
[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules



EN 60947-1/A1 (2011)
[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules



EN 60947-3/A1 (2011)
 [European Standard] Low-voltage
 switchgear and controlgear Part 3:
 Switches, disconnectors, switch-
 disconnectors and fuse-combination units



EN 60947-1/A2 (2014)
 [European Standard] Low-voltage
 switchgear and controlgear - Part 1: General
 rules



EN 60947-3/A2 (2015)
 [European Standard] Low-voltage
 switchgear and controlgear Part 3:
 Switches, disconnectors, switch-
 disconnectors and fuse-combination units

Packaging

Description	Carton
Quantity	1
EAN code	
Gross weight	0 KG
Volume	0
Dimensions	0x0x0 ()

Annexed



Instruction manual



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

Note:

- > Handle padlockable in OFF only (3 padlocks) 
- > TOP/BOTTOM = Top/Bottom connection 
- > Equipped with door interlock 
- > With late break and early make neutral pole 
- > Gland plate cable entry 
- > Fuses not supplied 