

**Article**

**805.RL75.S**  
 NUT St- 75-M75x1,5

**Picture****Master data**

|                                 |               |
|---------------------------------|---------------|
| Minimum order                   | 1 NR          |
| Net Weight                      | 0 G           |
| EAN code                        | 8001636254340 |
| Harmonized System Code (HSCode) | 73269098      |

**TechData**

|                            |                    |
|----------------------------|--------------------|
| Commercial series          | UNION-EX Series    |
| Synthetical description    | LOCK NUT           |
| Protection degree IP       | IP66/IP68          |
| Thread                     | M75X1,5            |
| Group and categories EX    | II 2 GD            |
| Group and categories EX    | IM 2               |
| Gas protection mode        | Ex d I Mb          |
| Gas protection mode        | Ex d IIC Gb        |
| Gas protection mode        | Ex e I Mb          |
| Gas protection mode        | Ex e IIC Gb        |
| Dust protection            | Ex tc IIIC Db IP66 |
| Ambient temperature Ta min | -40 °C             |
| Ambient temperature Ta max | 100 °C             |

**Approvals and Certifications****Packaging**

|             |     |
|-------------|-----|
| Description | Bag |
| Quantity    | 10  |

**Standards and Laws****Annexed**

Technical drawing [DWG]

|              |               |
|--------------|---------------|
| EAN code     | 8001636700656 |
| Gross weight | 0 G           |
| Volume       | 0             |
| Dimensions   | 0x0x0 ()      |
|              |               |



Technical drawing [PDF]



Technical drawing [STP]