

Article**899.IN25087**

INTERLOCK.SOCKET 3P+N+E IP65 250A 690V

Picture**Master data**

Minimum order	1 NR
Net Weight	21.2 KG
EAN code	8001636315508
Harmonized System Code (HSCode)	85366990

TechData

Commercial series	OPTIMA-METAL Series
Synthetical description	INTERLOCKED SOCKET
Rated current	250A
Poles	3P+N+E
Rated voltage	690V
Protection degree IP	IP65

Approvals and Certifications
 UE
 Declaration of conformity
Standards and Laws
 EN 60309-1 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements

 EN 60309-1/A1 (2007)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements

 EN 60947-3 (2006)
 [European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units

 EN 60947-3/A1 (2011)
 [European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units

 EN 60309-1/A2 (2012)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60947-1/A2 (2014)
 [European Standard] Low-voltage
 switchgear and controlgear - Part 1: General
 rules



EN 60947-3/A2 (2015)
 [European Standard] Low-voltage
 switchgear and controlgear Part 3:
 Switches, disconnectors, switch-
 disconnectors and fuse-combination units

Packaging

Description	Carton
Quantity	1
EAN code	
Gross weight	23.8 KG
Volume	149688 CCM
Dimensions	420x540x660 (MM)

Annexed



Instruction manual



Wiring diagram



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]



Note:

> To be mated with HDAL250 plugs



> Application example

