

SITOR fuse holder 50 A 690 V 1-pole with bolt terminal with fixing dimension 75 mm



Model	
product brand name	SENTRON
Product designation	LV HRC fuse system
Design of the thread / of the connection screw	M5
Design of the product	LV HRC fuse base for screw fixing
General technical data	
number of poles	1
Usage category	Without
Supply voltage	
Operating current / at AC / rated value	50 A
Supply voltage	
• at AC / rated value	690 V
• at DC	690 V
Current	
Tripping residual / rated value / derated current / at 40 Cel	46 A
Product details	

Product component / Swivel mechanism	No
--------------------------------------	----

### Connections

Tightening torque / with screw-type terminals / maximum	2 N·m
<ul style="list-style-type: none"> <li>• type of electrical connection</li> </ul>	for mounting on mounting plate
<ul style="list-style-type: none"> <li>• Type of electrical connection / for main current circuit</li> </ul>	Stud terminal

### Mechanical Design

Height	98 mm
Width	28 mm
Mounting type	fixed mounting
Mounting type <ul style="list-style-type: none"> <li>• bus-mounting</li> </ul>	No
net weight	187 g

### Certificates

<ul style="list-style-type: none"> <li>• reference code / acc. to DIN EN 61346-2</li> </ul>	F
<ul style="list-style-type: none"> <li>• Reference code / acc. to DIN EN 81346-2</li> </ul>	F

### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3NH5723>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3NH5723>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mfb=3NH5723](http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=3NH5723)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>

