

Solid-state contactor 3-phase 3RF2 AC 51 / 30 A / 40 °C 48-600 V / 4-30 V DC 2-phase controlled screw terminal Blocking voltage 1200 V



<b>Product brand name</b>	SIRIUS
<b>Product designation</b>	solid-state contactor
<b>Product type designation</b>	3RF24
<b>Manufacturer's article number</b>	
<ul style="list-style-type: none"> <li>• <u>2</u> / of the accessories that can be ordered</li> </ul>	<a href="#">3RF2900-0EA18</a>
<b>Product designation</b>	
<ul style="list-style-type: none"> <li>• <u>2</u> / of the accessories that can be ordered</li> </ul>	converter

General technical data	
<b>Product function</b>	zero-point switching
Power loss [W] / for rated value of the current / at AC / in hot operating state	61 W
<b>Insulation voltage</b>	
<ul style="list-style-type: none"> <li>• rated value</li> </ul>	600 V
<b>Degree of pollution</b>	3
<b>Protection class IP</b>	IP20
Shock resistance / acc. to IEC 60068-2-27	15g / 11 ms
Vibration resistance / acc. to IEC 60068-2-6	2g
<b>Reference code / acc. to DIN EN 81346-2</b>	Q

### Main circuit

<b>Number of poles / for main current circuit</b>	3
<b>Number of NO contacts / for main contacts</b>	2
<b>Number of NC contacts / for main contacts</b>	0
<b>Operating voltage / at AC</b>	
• at 50 Hz / rated value	48 ... 600 V
• at 60 Hz / rated value	48 ... 600 V
<b>Operating frequency / rated value</b>	50 ... 60 Hz
<b>Relative symmetrical tolerance / of the operating frequency</b>	10 %
<b>Operating range relative to the operating voltage / at AC</b>	
• at 50 Hz	40 ... 660 V
• at 60 Hz	40 ... 660 V
<b>Operating current</b>	
• at AC-51 / rated value	30 A
• acc. to UL 508 / rated value	22 A
<b>Operating current / minimum</b>	500 mA
<b>Rate of voltage rise / at the thyristor / for main contacts / maximum permissible</b>	1 000 V/ $\mu$ s
<b>Blocking voltage / at the thyristor / for main contacts / maximum permissible</b>	1 200 V
<b>Reverse current / of the thyristor</b>	10 mA
<b>Derating temperature</b>	40 °C
<b>Surge current resistance / rated value</b>	1 200 A
<b>I<sup>2</sup>t value / maximum</b>	7 200 A <sup>2</sup> ·s

#### Control circuit/ Control

<b>Type of voltage / of the control supply voltage</b>	DC
<b>Control supply voltage / 1</b>	
• at DC / rated value	30 V
• at DC	4 ... 30 V
<b>Control supply voltage</b>	
• at DC / initial value for signal <1> detection	4 V
• at DC / Full-scale value for signal <0> recognition	1 V
<b>Symmetrical line frequency tolerance</b>	5 Hz
<b>Control current / at minimum control supply voltage</b>	
• at DC	22 mA
<b>Control current / at DC / rated value</b>	30 mA
<b>Switch-on delay time</b>	1 ms; additionally max. one half-wave
<b>Number of NC contacts / for auxiliary contacts</b>	0
<b>Number of NO contacts / for auxiliary contacts</b>	0
<b>Number of CO contacts / for auxiliary contacts</b>	0

#### Installation/ mounting/ dimensions

<b>Mounting type</b>	screw and snap-on mounting onto 35 mm standard mounting rail
• Side-by-side mounting	Yes
<b>Height</b>	100 mm
<b>Width</b>	74.5 mm; 90.5 mm product version E01
<b>Depth</b>	115.6 mm; 112.5 mm product version E01
<b>Installation altitude / at height above sea level / maximum</b>	1 000 m

## Connections/ Terminals

<b>Type of connectable conductor cross-sections</b>	
• for main contacts	
— solid	2x (1.5 ... 2.5 mm <sup>2</sup> ), 2x (2.5 ... 6 mm <sup>2</sup> )
— finely stranded / with core end processing	2x (1 ... 2.5 mm <sup>2</sup> ), 2x (2.5 ... 6 mm <sup>2</sup> ), 1x 10 mm <sup>2</sup>
• at AWG conductors / for main contacts	2x (14 ... 10)
<b>Type of connectable conductor cross-sections</b>	
• for auxiliary and control contacts	
— solid	1x (0.5 ... 2.5 mm <sup>2</sup> ), 2x (0.5 ... 1.0 mm <sup>2</sup> )
— finely stranded / with core end processing	1x (0.5 ... 2.5 mm <sup>2</sup> ), 2x (0.5 ... 1.0 mm <sup>2</sup> )
— finely stranded / without core end processing	1x (0.5 ... 2.5 mm <sup>2</sup> ), 2x (0.5 ... 1.0 mm <sup>2</sup> )
• at AWG conductors / for auxiliary and control contacts	1x (AWG 20 ... 12)
<b>Tightening torque</b>	
• for main contacts / with screw-type terminals	2 ... 2.5 N·m
• for auxiliary and control contacts / with screw-type terminals	0.5 ... 0.6 N·m
<b>Tightening torque [lbf·in]</b>	
• for main contacts / with screw-type terminals	18 ... 22 lbf·in
• for auxiliary and control contacts / with screw-type terminals	7.5 ... 5.3 lbf·in
<b>Design of the thread / of the connection screw</b>	
• for main contacts	M4
• of the auxiliary and control contacts	M3
<b>Wire stripping length / of the cable</b>	
• for main contacts	7 mm
• for auxiliary and control contacts	7 mm

## Ambient conditions

<b>Ambient temperature</b>	
• during operation	-25 ... +60 °C
• during storage	-55 ... +80 °C

## Electromagnetic compatibility






<b>Conducted interference</b>	
• due to burst / acc. to IEC 61000-4-4	2 kV / 5 kHz behavior criterion 2

<ul style="list-style-type: none"> <li>• due to conductor-earth surge / acc. to IEC 61000-4-5</li> <li>• due to conductor-conductor surge / acc. to IEC 61000-4-5</li> <li>• due to high-frequency radiation / acc. to IEC 61000-4-6</li> </ul>	<p>2 kV behavior criterion 2</p> <p>1 kV behavior criterion 2</p> <p>140 dBuV in the frequency range 0.15 ... 80 MHz, behavior criterion 1</p>
<b>Electrostatic discharge / acc. to IEC 61000-4-2</b>	4 kV contact discharging / 8 kV air discharging, behavior criterion 2
<b>Conducted HF-interference emissions / acc. to CISPR11</b>	Class A for industrial environment
<b>Field-bound HF-interference emission / acc. to CISPR11</b>	Class A for industrial environment

### Short-circuit protection, design of the fuse link

<p>Manufacturer's article number</p> <ul style="list-style-type: none"> <li>• of full range R fuse link for semiconductor protection / at NH design</li> <li>• of full range R fuse link for semiconductor protection / at cylindrical design</li> <li>• of back-up R fuse link for semiconductor protection / at NH design</li> <li>• of back-up R fuse link for semiconductor protection / at cylindrical design 10 x 38 mm</li> <li>• of back-up R fuse link for semiconductor protection / at cylindrical design 14 x 51 mm</li> <li>• of back-up R fuse link for semiconductor protection / at cylindrical design 22 x 58 mm</li> </ul>	<p><a href="#">3NE1803-0</a></p> <p><a href="#">5SE1335; Maximum operating voltage 400 V!</a></p> <p><a href="#">3NE8003-1</a></p> <p><a href="#">3NC1032</a></p> <p><a href="#">3NC1450</a></p> <p><a href="#">3NC2280</a></p>
<p>Manufacturer's article number / of the gG fuse / at NH design</p> <ul style="list-style-type: none"> <li>• up to 460 V</li> </ul>	<p><a href="#">3NA3812</a></p>

### Certificates/ approvals

General Product Approval		EMC	Declaration of Conformity	
				
CSA	UL		RCM	EG-Konf.

[Miscellaneous](#)

Test Certificates	other
-------------------	-------

[Type Test Certificates/Test Report](#)

[Confirmation](#)



## Further information

### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3RF2430-1AB45>

### Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mfb=3RF2430-1AB45>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RF2430-1AB45>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mfb=3RF2430-1AB45&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mfb=3RF2430-1AB45&lang=en)

