

Indicator light, 16 mm, round, plastic, white, Lampholder W2 x 4.6 d, without lamp



Figure similar

Product brand name	SIRIUS
Product designation	Indicator lights
Design of the product	Complete unit round
Product type designation	3SB2
Enclosure	
Number of command points	0
Actuator	
Design of the operating mechanism	indicator light
Product extension optional Light source	Yes
Color	
• of the actuating element	white
Material of the actuating element	plastic
Type of unlocking device	without
Number of switching positions	2
Front ring	
Product component front ring	No

Holder	
Material of the holder	Plastic
Contact block/ lampholder	
Mounting type	W2 x 4.6d without lamp
Number of lampholders	1
Number of switching elements	0
General technical data	
Product function	
<ul style="list-style-type: none"> positive opening EMERGENCY STOP function 	No No
Product component	
<ul style="list-style-type: none"> Light source 	No
Type of voltage	
<ul style="list-style-type: none"> of the operating voltage 	AC/DC
Protection class IP	IP65
Vibration resistance	
<ul style="list-style-type: none"> acc. to IEC 60068-2-6 	20 ... 200 Hz: 5g
Reference code acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	H
Reference code acc. to DIN EN 81346-2	P
Reference code acc. to DIN EN 61346-2	P
Operating voltage	
<ul style="list-style-type: none"> rated value 	5 ... 60 V
Auxiliary circuit	
Number of NC contacts for auxiliary contacts	0
Number of NO contacts for auxiliary contacts	0
Number of CO contacts	
<ul style="list-style-type: none"> for auxiliary contacts 	0
Connections/ Terminals	
Type of electrical connection	tab terminals
Tightening torque of the screws in the bracket	0.4 N·m
Ambient conditions	
Ambient temperature	
<ul style="list-style-type: none"> during operation during storage 	-25 ... +60 °C -40 ... +80 °C
Environmental category during operation acc. to IEC 60721	3K6
Installation/ mounting/ dimensions	
Mounting type	front panel mounting
Shape of the installation opening	round

Mounting diameter	16 mm
Mounting height	9 mm
Installation width	19 mm
Installation depth	50 mm

Certificates/ approvals

General Product Approval

Declaration of Conformity



[Miscellaneous](#)

Test Certificates

other

Railway

[Special Test Certificate](#)

[Miscellaneous](#)

[Confirmation](#)

[Special Test Certificate](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB2204-6BG06>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB2204-6BG06>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB2204-6BG06>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB2204-6BG06&lang=en

last modified:

08/06/2020