SIEMENS

Data sheet

3TK1910-3A

| | 1st auxiliary switch block for lateral mounting to contactors left or right 1 NO + 1 NC | | |
|---|---|--|--|
| General technical data | | | |
| product brand name | SIRIUS | | |
| suitability for use | Contactor relay and power contactor | | |
| protection class IP on the front | IP20 | | |
| ambient temperature | | | |
| during storage | -55 +80 °C | | |
| during operation | -25 +55 °C | | |
| mechanical service life (switching cycles) typical | 10 000 000 | | |
| insulation voltage with degree of pollution 3 at AC rated value | 690 V | | |
| surge voltage resistance rated value | 6 kV | | |
| Auxiliary circuit | | | |
| number of NC contacts for auxiliary contacts | | | |
| instantaneous contact | 1 | | |
| lagging switching | 0 | | |
| number of NO contacts for auxiliary contacts | | | |
| instantaneous contact | 1 | | |
| leading contact | 0 | | |
| operational current of auxiliary contacts at AC-12 | | | |
| • at 24 V | 10 A | | |
| • at 230 V | 10 A | | |
| • maximum | 10 A | | |
| operational current | | | |
| of auxiliary contacts | | | |
| — at AC-14 | | | |
| — at 125 V | 10 A | | |
| — at AC-15 | | | |
| — at 24 V | 10 A | | |
| — at 230 V | 5.6 A | | |
| — at 400 V | 3.6 A | | |
| at AC-15 at 690 V rated value | 2.3 A | | |
| operational current | | | |
| of auxiliary contacts at DC-13 | | | |
| — at 24 V | 10 A | | |
| — at 60 V | 5 A | | |
| — at 110 V | 1.14 A | | |
| — at 220 V | 0.48 A | | |
| Installation/ mounting/ dimensions | | | |
| fastening method | snap-on mounting | | |
| width | 12 mm | | |
| height | 70 mm | | |
| depth | 51.5 mm | | |
| Connections/ Terminals | | | |
| type of connectable conductor cross-sections | | | |
| for auxiliary contacts | | | |
| — finely stranded | | | |
| — with core end processing | 2x (0.5 1.0 mm²), 2x (0.75 2.5 mm²) | | |
| at AWG cables for auxiliary contacts | 2x (18 12) | | |
| Safety related data | | | |
| product function positively driven operation | Yes | | |
| 1 | | | |

| according to IEC 60 | 947-5-1 | | | | | | |
|-------------------------|---------|---------------------------|---|---------------------|--|--|--|
| Certificates/ approvals | | | | | | | |
| General Product Ap | proval | Declaration of Conformity | | other | | | |
| | EAC | C C EG-Konf. | <u>UK Declaration of</u> <u>Conformity</u> | <u>Confirmation</u> | | | |

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TK1910-3A

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TK1910-3A

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3TK1910-3A

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TK1910-3A&lang=en

last modified:

1/8/2021 🖸