

[NEOZED-Sicherungseinsatz], D01, 10 A, [gG], Un AC: 400 V, Un DC: 250 V, [mit verzinnnten Kontaktkappen]



Model	
product brand name	SETRON
Product designation	NEOZED fuse link
Design of the product	With tin-coated contact caps
product variations	Pack of 10
Design of the fuse link	NEOZED fuse link

General technical data	
Size of fuse system / acc. to DIN EN 60269-1	D01
Operating class of the fuse link	gG

Supply voltage	
Operating current / at AC / rated value	10 A
Supply voltage	
• at AC / rated value	400 V
• at DC	250 V
Operating voltage / rated value	400 V
Protection class IP	IP20, with connected conductors
Switching capacity current / acc. to IEC 60947-2 / rated value	50 kA

Dissipation

Power loss [W] / for rated value of the current / at AC
/ in hot operating state / per pole

1 W

Main circuit

Operating current / rated value

10 A

Appearance

Color coding of the fuse link

Red

Maximum short-circuit current breaking capacity (I_{cu})
/ at AC / rated value

50 kA

Mechanical Design

mounting position

Any, preferably vertical

net weight

7 g

Ambient temperature

• minimum

-5 °C

• maximum

40 °C

Environmental category

Up to 45°C at 95 % rel. humidity

Certificates

• reference code / acc. to DIN EN 61346-2

F

• Reference code / acc. to DIN EN 81346-2

F

General Product Approval

Declaration of Conformity

Test Certificates



ÖVE



VDE



EG-Konf.

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

[Miscellaneous](#)

other

[Environmental Conformations](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SE2310>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SE2310>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SE2310

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

