

Connection terminal Cable entry right 690V AC, 1000 V DC, 80 A
IP20



Figure similar

Model	
product brand name	SETRON
Product designation	Busbar systems
Design of the product	Accessories
Operating current / at AC / rated value	80 A
Operating voltage / at AC / rated value	690 V

Connections	
Tightening torque	
• minimum	1 N·m
• maximum	2 N·m
Type of connectable conductor cross-sections / for copper conductor / stranded	6 - 25 mm ²

Mechanical Design	
Height	17.7 mm
Width	17.5 mm
Depth	13 mm
length	26.5 mm

net weight

13.5 g

Certificates

General Product Approval

Declaration of Conformity

[Miscellaneous](#)



EG-Konf.

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3768-5>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3768-5>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3768-5

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>