

DELTA i-system Time switch runtime 15min 250 V 16 A 2-pole can be switched off for screw mounting titanium white, 55x 55 mm



Model	
product brand name	SENTRON
Design of the switching function	off 2-pole
Type of composition	basic element with central cover plates
General technical data	
Surface processing	other
Material	thermoset
Operating voltage / Rated value	250 V
Protection class	
Protection class IP	IP20
Switching capacity	
switching capacity current	16 A
Dissipation	
Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	3 500 W
Main circuit	
Operating current / rated value	16 A

Adjustable parameters

adjustable time	
• initial value	0.5 min
• Full-scale value	15 min

Appearance

Appearance	polished
RAL color number	RAL 9010
Color	white

Product details

Number of NC contacts	0
Number of NO contacts	2
Number of CO contacts	0
• product feature / halogen-free	Yes
• Product feature / transparent	No

Mechanical Design

Mounting type	flush mounting
net weight	173 g
Material / of the enclosure	plastic

Certificates

Declaration of Conformity



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TT1011>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5TT1011>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TT1011

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

