SIEMENS

Data sheet

6AV6676-6MB20-3AX0



SIMATIC MODBUS/TCP PN-CPU Single license, on CD-ROM

General information	
Engineering with	
 STEP 7 TIA Portal configurable/integrated from version 	V13
 STEP 7 configurable/integrated from version 	STEP 7 V5.5 or higher
 PCS 7 configurable/integrated from version 	PCS 7 V7.1 SP2
Redundancy	
 Redundancy capability 	No
Protocols	
SIMATIC communication	
 Communication as Modbus server 	Yes
 Communication as Modbus client 	Yes
 User data per job (of which consistent), max. 	250 byte
Operating systems	
Runs under operating system	
Windows XP	Yes
• Windows 7	Yes
Software	
Runtime software	
Target system	
— ET 200S	Yes; FW V3.2 or higher
— ET 200pro	Yes; FW V3.2 or higher
— S7-300	Yes; FW V3.2 or higher
— S7-400	Yes; FW V6.0 or higher
— WinAC	No
 — Suitable for other target system 	Yes; See:
	https://support.industry.siemens.com/cs/ww/en/view/104946406
Block	
Local data requirements	156 byte
FB length in RAM, max.	19 kbyte
Multi-instance capable	Yes
Communication data	Ver
Multiport	Yes
Client-server coupling	SIMATIC S7 as master or slave
implemented function codes	01, 02, 03, 04, 05, 06, 15, 16
Authorization/licenses	Vec
Single license (EL)	Yes
configuration / header	
Configuration software	

 Wizard for configuration support 	Yes; Wizard
configuration / programming / header	
Programming language	
— LAD	Yes
— FBD	Yes
— STL	Yes
— SCL	Yes
— CFC	Yes
— GRAPH	Yes
Configuration examples	
— STL example project	Yes
— CFC example project	Yes
Documentation	
Languages	
• German	Yes; Electronic, included on CD
• English	Yes; Electronic, included on CD

last modified:

1/19/2021 🖸