

stairwell lighting timer w/ advance warning via short-time interruption for 230V contact 2000W



Figure similar

Model	
product brand name	SENTRON
Product designation	Timers
Design of the product	Staircase lighting timer
General technical data	
Switch-off prewarning	flashing
Manner of function / of the staircase lighting switch	manual
Short-circuit current rating	700 A
Voltage	
Staircase lighting timing switch reset function	resettable
Supply voltage	
Supply voltage / at AC	
• minimum	230 V
• maximum	230 V
Type of voltage / of the supply voltage	AC
Switching capacity	

Switching capacity apparent power	
<ul style="list-style-type: none"> <li>• for fluorescent lamp load with DUO circuit</li> <li>• for uncompensated fluorescent lamp load</li> </ul>	1 160 V·A
Switching capacity current	
<ul style="list-style-type: none"> <li>• at cos phi 0.6</li> <li>• Rated value</li> </ul>	16 A
Switching capacity active power / with filament lamp load	2 000 W

<b>Dissipation</b>	
Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	5 W

<b>Current</b>	
Consumed current / of the light source	50 mA
Connection method for staircase lighting timer switch	3- and 4-wire-circuit

<b>Control current</b>	
Type of voltage	
<ul style="list-style-type: none"> <li>• of control voltage_1</li> </ul>	AC
Control voltage	
<ul style="list-style-type: none"> <li>• _1 / initial value</li> <li>• _1 / Full-scale value</li> </ul>	230 V
Control voltage frequency	
<ul style="list-style-type: none"> <li>• _1 / initial value</li> <li>• _1 / Full-scale value</li> </ul>	50 Hz

<b>Adjustable parameters</b>	
adjustable OFF-delay time	
<ul style="list-style-type: none"> <li>• initial value</li> <li>• Full-scale value</li> </ul>	0.5 min
Number of NC contacts	0
Number of NO contacts	1
Number of CO contacts	0

<b>Mechanical Design</b>	
Height	90 mm
Width	18 mm
Depth	64 mm
installation depth	64 mm
number of width units	1
Mounting type	DIN-busbar
net weight	88 g

<b>Certificates</b>	
<ul style="list-style-type: none"> <li>• reference code / acc. to DIN EN 61346-2</li> </ul>	K

Declaration of Conformity

other



EG-Konf.

[Environmental Confirmations](#)

## Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7LF6113>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/7LF6113>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=7LF6113](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7LF6113)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>

