

SENTRON, cylindrical fuse link, 14x51 mm, 8 A, aM, Un AC: 690 V



Versão	
nome da marca do produto	SENTRON
designação do produto	Encaixe de fusível cilíndrico
Dados técnicos gerais	
Classe de operação do elemento fusível	aM
Tamanho do elemento fusível	14x51 mm
Tipo de tensão	CA
corrente de serviço / com AC / valor estipulado	8 A
Tensão de alimentação / com DC	250 V
Tensão de serviço / valor estipulado	690 V
Dissipação	
Potência de perda [W] / com valor de corrente estipulado / com AC / com estado de funcionamento quente / por polo	0,55 W
Circuito principal	
corrente de serviço	
• valor nominal	8 A
Detalhes do produto	

Componente do produto / Detetor de choque	Não
---	-----

Projeto mecânico

posição de montagem	opcional, preferível vertical
peso líquido	18 g

Certificados

indicadores de referência	
<ul style="list-style-type: none"> segundo a DIN EN 61346-2 	F
<ul style="list-style-type: none"> segundo a IEC 81346-2:2009 	F

Declaration of Conformity	Test Certificates
----------------------------------	--------------------------



[Miscellaneous](#)

Outras informações

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/pt/pt/Catalog/product?mlfb=3NW8108-1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/pt/ps/3NW8108-1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NW8108-1

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

