

<ul style="list-style-type: none"> • Switching between operating modes in RUN 	Yes; For module version 32 I/20 Q, it is possible to dynamically switch between 25 user data variants, 23 of which are pre-defined and 2 of which can be defined by the specific user
<ul style="list-style-type: none"> • Cyclic measured value access 	Yes
<ul style="list-style-type: none"> • Acyclic measured value access 	Yes
<ul style="list-style-type: none"> • Fixed measured value sets 	Yes
<ul style="list-style-type: none"> • Freely definable measured value sets 	Yes; For cyclic and acyclic measured value access
CiR - Configuration in RUN	
Reparameterization possible in RUN	Yes
Calibration possible in RUN	Yes
Installation type/mounting	
Mounting position	any
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	12.5 mA
Current consumption, max.	17 mA
Power loss	
Power loss, typ.	400 mW; 3x 230 V AC
Address area	
Address space per module	
<ul style="list-style-type: none"> • Inputs 	256 byte
<ul style="list-style-type: none"> • Outputs 	20 byte
Hardware configuration	
Automatic encoding	Yes
<ul style="list-style-type: none"> • Mechanical coding element 	Yes
<ul style="list-style-type: none"> • Type of mechanical coding element 	type C
Selection of BaseUnit for connection variants	
<ul style="list-style-type: none"> • 2-wire connection 	BU type U0
Time of day	
Operating hours counter	
<ul style="list-style-type: none"> • present 	Yes
Analog inputs	
Cycle time (all channels), typ.	50 ms; Time for consistent update of all measured and calculated values (cyclic und acyclic data)
Cable length	
<ul style="list-style-type: none"> • shielded, max. 	200 m
<ul style="list-style-type: none"> • unshielded, max. 	200 m
Analog value generation for the inputs	
Sampling frequency, max.	2 048 kHz
Interrupts/diagnostics/status information	
Alarms	
<ul style="list-style-type: none"> • Diagnostic alarm 	Yes
<ul style="list-style-type: none"> • Limit value alarm 	Yes
<ul style="list-style-type: none"> • Hardware interrupt 	Yes; Monitoring of up to 16 freely selectable process values (exceeding or undershooting of value)
Diagnoses	
<ul style="list-style-type: none"> • Line quality 	Yes
<ul style="list-style-type: none"> • Supply voltage 	Yes
<ul style="list-style-type: none"> • Hardware interrupt lost 	Yes
<ul style="list-style-type: none"> • Parameter assignment error 	Yes
<ul style="list-style-type: none"> • Module fault 	Yes
<ul style="list-style-type: none"> • Channel not available 	Yes
<ul style="list-style-type: none"> • Overflow/underflow 	Yes
<ul style="list-style-type: none"> • Overload current 	Yes
Diagnostics indication LED	
<ul style="list-style-type: none"> • Monitoring of the supply voltage (PWR-LED) 	Yes

• Channel status display	Yes; green LED
• for channel diagnostics	Yes; red Fn LED
• for module diagnostics	Yes; green/red DIAG LED

Integrated Functions

Measuring functions	
• Measuring procedure for voltage measurement	TRMS
• Measuring procedure for current measurement	TRMS
• Type of measured value acquisition	seamless
• Curve shape of voltage	Sinusoidal or distorted
• Buffering of measured variables	Yes
• Parameter length	128 byte
• Bandwidth of measured value acquisition	3.2 kHz; Harmonics: 63 / 50 Hz, 52 / 60 Hz
Measuring range	
— Frequency measurement, min.	40 Hz
— Frequency measurement, max.	70 Hz
Measuring inputs for voltage	
— Measurable line voltage between phase and neutral conductor	277 V
— Measurable line voltage between the line conductors	480 V
— Measurable line voltage between phase and neutral conductor, min.	3 V
— Measurable line voltage between phase and neutral conductor, max.	300 V
— Measurable line voltage between the line conductors, min.	6 V
— Measurable line voltage between the line conductors, max.	519 V
— Internal resistance line conductor and neutral conductor	1.5 MΩ
— Power consumption per phase	60 mW; 300 V AC
— Impulse voltage resistance 1,2/50μs	2.5 kV
— Overvoltage category	CAT II according to IEC 61010 Part 1
Measuring inputs for current (Rog. or I/U converter)	
— Measurable current at AC, max.	424 mA
— Continuous voltage, maximum permissible	2 V
— Rated value, short-time withstand voltage restricted to 1 s	30 V
— Input resistance	120 kΩ
— Zero point suppression	Yes; 0 ... 20%, referred to the nominal current
Accuracy class according to IEC 61557-12	
— Measured variable voltage	0,2
— Measured variable current	0,2
— Measured variable apparent power	0.5
— Measured variable active power	0.5
— Measured variable reactive power	1
— Measured variable power factor	0.5
— Measured variable active energy	0.5
— Measured variable reactive energy	1
— Measured variable neutral current	0,2
— Measured variable phase angle	±0.5 °; not covered by IEC 61557-12
— Measured variable frequency	0.05; only valid for the permissible voltage measuring range
— Measured variable harmonic	1
— Measured variable THDU	1
— Measured variable THDI	1
Accuracy class line analysis acc. to IEC 61000-4-30	
— Measured variable voltage	Class S
— Measured variable current	Class S
— Measured variable frequency	Class S
— Measured variable voltage interruption	Class S
— Measured variable voltage dip and swell	Class S
— Measured variable harmonic voltage	Class S

— Measured variable harmonic current

Class S

Potential separation

Potential separation channels

- | | |
|--|-------------------|
| • between the channels | No |
| • between the channels and backplane bus | Yes |
| • Between the channels and load voltage L+ | Yes; Including FE |

Isolation

Isolation tested with	Between channels and backplane bus, 24 V supply: Routine test, 1 920 V AC, 2 s; between backplane bus and 24 V supply: Type test, 707 V DC
-----------------------	--

Ambient conditions

Ambient temperature during operation

- | | |
|---------------------------------|--------|
| • horizontal installation, min. | -30 °C |
| • horizontal installation, max. | 60 °C |
| • vertical installation, min. | -30 °C |
| • vertical installation, max. | 50 °C |

Altitude during operation relating to sea level

- | | |
|---|--|
| • Installation altitude above sea level, max. | 3 000 m; Restrictions for installation altitudes > 2 000 m, see manual |
|---|--|

Dimensions

Width	20 mm
Height	73 mm
Depth	58 mm

Weights

Weight, approx.	45 g
-----------------	------

Other

Data for selecting a voltage transformer

- | | |
|------------------------|-------|
| • Secondary side, max. | 300 V |
|------------------------|-------|

last modified:

1/24/2022 